

PRODUCT SPECIFICATIONS:

PILE CONTENT:	50% Wool, 50% Synthetic Featuring TEXTURE LOC ®
PILE WEIGHT:	881 gm/m ² - 26 oz/yd ²
PILE HEIGHT:	6 mm
CARPET THICKNESS:	8 mm
MACHINE GAUGE:	2.54 mm - 1/10"
STITCH RATE:	As required to provide a carpet of total pile mass, pile height and machine gauge as specified.
WIDTH:	3.66 metres
PRIMARY BACK:	Heat Stabilised Woven Polypropylene
SECONDARY BACK:	Woven Jute
FIRE RATING:	AS/ISO 9239.1:2003
GRADING:	Residential Heavy Duty & Stairs
ENVIRONMENTAL ACCREDITATION:	Achieves Certification under the ACCS Environmental Classification Scheme.
VOC EMISSIONS:	Meets ACCS Environmental Classification Criteria
COMMERCIAL WARRANTY:	7 Year Limited Manufacturers Defect Warranty
TOLERANCE:	Manufactured to A.S. 1385 tolerances.
INSTALLATION:	To be laid in accordance with AS/NZS 2455.1:2007 Seam sealer must be applied to all seams (prior to joining).
COLOUR VARIATION:	Colour variation may occur between sample and production due to dye lot tolerances.
MATERIAL VARIATION:	Product specifications may change without notice due to raw material availability.
SHADING: (Permanent Pile Reversal)	Cut pile carpets have a propensity to shade. This is not a manufacturing fault further information can be obtained from the Carpet Institute of Australia leaflet.
COUNTRY OF MANUFACTURE:	Australia