

TERELLE TWIST

PRODUCT SPECIFICATIONS:

PILE CONTENT:	100% SDN
PILE WEIGHT:	2200 gm/m ² - 66 oz/yd ²
PILE HEIGHT:	15mm
CARPET THICKNESS:	17mm
MACHINE GAUGE:	3.175mm - 1/8"
STITCH RATE:	As required to provide a carpet of total pile mass, pile height and machine gauge as specified.
WIDTH:	3.66 metres
PRIMARY BACK:	Heat Stabilised Woven Polypropylene
SECONDARY BACK:	Synthetic Don Bac
GRADING:	Residential Extra Heavy Duty & Stairs Contract Medium Duty & Stairs
VOC EMISSIONS:	Meets ACCS Environmental Classification Criteria
RESIDENTIAL WARRANTY:	15 Year Limited Residential Wear Warranty
TOLERANCE:	Manufactured to A.S. 1385 tolerances.
INSTALLATION:	To be laid in accordance with AS/NZS 2455.1:2007 Seam sealer must be applied to all seams (prior to joining).
COLOUR VARIATION:	Colour variation may occur between sample and production due to dye lot tolerances.
MATERIAL VARIATION:	Product specifications may change without notice due to raw material availability.
SHADING: (Permanent Pile Reversal)	Cut pile carpets have a propensity to shade. This is not a manufacturing fault. Further information can be obtained from the Carpet Institute of Australia.
COUNTRY OF MANUFACTURE:	Australia