

# COLOUR STROKE PLANK

## PRODUCT SPECIFICATIONS

Product Description	Textured Loop
Fibre	nexlon™ Premium Nylon with recycled content
Dye Method	Solution Dyed
Pile Weight	600 g/m <sup>2</sup> - 18 oz
Machine Gauge	1/12"
Pile Height	High 5 mm to Low 3 mm
Total Thickness	7 mm
Backing	Recycled Tuntex Duraback
Tile Size	250mm x 1000mm
Installation Method	Various
Adhesive	To be laid in accordance with AS/NZS 2455:2007(Parts 1 & 2)
Anti-Static Performance	Full floor coverage with low VOC pressure sensitive adhesive
Dimensional Stability	AATCC 134 < 3.5kV
Fire Rating	< 0.2%
Area of Use	AS/ISO 9239.1:2003
Stain Resistance	Contract Heavy Duty & Stairs
Soil Resistance	stainShield treatment SOIL GUARD treatment

## ENVIRONMENTAL CREDENTIALS

Environmental Management System	ISO 14001:2015 certified (IQNet)
Environmental Accreditation	Achieves Level 4+ Certification under the ACCS Environmental Classification Scheme
Indoor Air Quality	VOC emission rates meet the criteria for the Green Label Plus and the Green Building Council of Australia.
Product Stewardship	Victoria Carpets, in partnership with our customer, will on a project by project basis, enter in to a contractual agreement to take back carpet at the end of its service life for reprocessing, reuse or recycling.

## WARRANTIES

15 Years Limited Warranties for Wear, Colourfastness, Anti-Static, Dimensional Stability and Manufacturing Defects

Specifications are subject to and may change without notice. Colour variation may occur between sample and production due to dye lot tolerances.



ISO 9001:2008  
ISO 14001:2015

Australia Freecall: 1800 136 040  
New Zealand Freecall: 0800 445 510

Email: sales@victoriacarpets.com.au  
www.victoriacarpets.com.au  
www.victoriacarpets.co.nz