## **SPECTRE**



## **PRODUCT SPECIFICATIONS**

Product Description Textured Loop

Fibre Premium Nylon with recycled content

Dye Method Solution Dyed
Pile Weight 600 g/m² - 18 oz

Machine Gauge 1/12"

Pile Height High 5 mm to Low 2.5 mm

Total Thickness 7.5 mm

Backing Recycled Tuntex Duraback

Tile Size 500mm x 500mm
Installation Method Quarter Turn Brick





To be laid in accordance with AS/NZS 2455:2007(Parts 1 & 2)

Full floor coverage with low VOC pressure sensitive adhesive

AATCC 134 < 3.5kV

< 0.2%

Fire Rating (AS/ISO 9239.1:2003) Critical Radiant Flux 7.5 kW/m<sup>2</sup>
Area of Use Contract Heavy Duty & Stairs

Stain Resistance stain Shield treatment
Soil Resistance Soil Guard treatment

## **ENVIRONMENTAL CREDENTIALS**

Environmental Management System ISO 14001:2015 certified (IQNet)

Environmental Accreditation Achieves Level 4+ Certification under the ACCS Environmental

Classification Scheme

Indoor Air Quality VOC emission rates meet the criteria for the Green Label Plus

and the Green Building Council of Australia.

Product Stewardship Victoria Carpets, in partnership with our customer, will on a

project by project basis, enter into a contractual agreement to take back carpet at the end of its service life for reprocessing,

reuse or recycling.

## **WARRANTIES**

Adhesive

**Anti-Static Performance** 

**Dimensional Stability** 

15 Years Limited Warranties for Wear, Colourfastness, Anti-Static, Dimensional Stability and Manufacturing Defects

Specifications are subject to and may change without notice. Colour variation may occur between sample and production due to dye lot tolerances.









ISO 9001:2008 ISO 14001:2015 Australia Freecall: 1800 136 040 New Zealand Freecall: 0800 445 510

> Email: sales@victoriacarpets.com.au www.victoriacarpets.com.au www.victoriacarpets.co.nz