

WAVELENGTH CUSHION

PRODUCT SPECIFICATIONS

Product Description	Hi / Lo Loop
Fibre	Solution Dyed Nylon
Pile Weight	500 g/m ² - 15oz
Machine Gauge	1/12"
Pile Height	High 3.5mm – Low 3.0mm
Total Thickness	8mm
Backing	Non-Woven Recycled Cushion Back
Tile Size	500mm x 500mm
Installation Method	Brick Quarter Turn



Adhesive	To be laid in accordance with AS/NZS 2455:2007(Parts 1 & 2)
Anti-Static Performance	Full floor coverage with low VOC pressure sensitive adhesive
Dimensional Stability	AATCC 134 < 3.5kV
Fire Rating (AS/ISO 9239.1:2003)	< 0.2%
Area of Use	Critical Radiant Flux 8.5 kW/m ²
Packaging	Contract Heavy Duty & Stairs
	4m ² per box

ENVIRONMENTAL CREDENTIALS

Environmental Management System	ISO 14001:2015 certified
Indoor Air Quality	VOC emission rates meet the criteria for the Green Label Plus.
Product Stewardship	Victoria Carpets, in partnership with our customer, will on a project-by-project basis, enter into a contractual agreement to take back carpet at the end of its service life for reprocessing, reuse or recycling.

WARRANTIES

15 Years Limited Warranties for Wear, Colourfastness, Anti-Static, Dimensional Stability and Manufacturing Defects

Specifications are subject to and may change without notice. Colour variation may occur between sample and production due to dye lot tolerances.



ISO 9001:2015
ISO 14001:2015

Australia Freecall: 1800 136 040
New Zealand Freecall: 0800 445 510

Email: sales@victoriacarpets.com.au
www.victoriacarpets.com.au
www.victoriacarpets.co.nz